

Ledinaire Waterproof Tube Housing

WT050C 1xTLED L1500

Ledinaire Waterproof Tube Housing, L1500 mm, IP65, IK08

The Ledinaire waterpprof (WT050C) range contains a selection of empty, waterproof housings, that can cater for LED tubes of your choice. It comes with the high Philips quality levels at a competitive price. Ledinaire enables, simple and quick installation, with a choice of single and double tube installations.

Product data

General Information	
Angle	-
Accessory color	Gray
Value ladder	Value

Light Technical	
Color rendering index (CRI)	-
Luminaire light beam spread	-

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz

Mechanical and Housing	
Overall length	1,580 mm
Overall width	69 mm
Overall height	70 mm
Dimensions (Height x Width x Depth)	70 x 69 x 1580 mm
Material	Polycarbonate

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class II
CE mark	CE mark


Product Data	
Order product name	WT050C 1xTLED L1500
Full product name	WT050C 1xTLED L1500
Full product code	871016336604399
Order code	911401807581
Material Nr. (12NC)	911401807581
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.880 kg
EAN/UPC - Product/Case	8710163366043
Numerator - Packs per outer box	12

Ledinaire Waterproof Tube Housing

EAN/UPC - Case	8710163366203

Dimensional drawing

WT050C L1500 1 Tube



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.