

LED

INTEGRATION FIXTURE

B4-1




35000 H

EEI : A+ BEAM ANGLE : 120° CRI : ≥80RA

PF : &gt;0.9 VOLTAGE : 100-240V

WORKING TEMPERATURE :-20°C-40°C

PACKING : 1PC/COLOR BOX  
40PC/CTN

| BARCODE | POWER | BRIGHTNESS | CURRENT | INCANDESCENT<br>LAMP POWER | IP   | MEAS              | CCT   | LIGHT COLOR   |
|---------|-------|------------|---------|----------------------------|------|-------------------|-------|---------------|
| 001956  | 36W   | 2900lm     | 180mA   | 290W                       | IP20 | L1200*W74.5*H23mm | 3000K | WARM WHITE    |
| 001963  | 36W   | 3000lm     | 180mA   | 300W                       | IP20 | L1200*W74.5*H23mm | 6000K | DAY LIGHT     |
| 002694  | 36W   | 2900lm     | 170mA   | 290W                       | IP20 | L1200*W74.5*H23mm | 4000K | NATURAL WHITE |
| 004902  | 50W   | 4150lm     | 230mA   | 400W                       | IP20 | L1500*W74*H23mm   | 4000K | NATURAL WHITE |
| 004919  | 50W   | 4150lm     | 230mA   | 400W                       | IP20 | L1500*W74*H23mm   | 6000K | DAY LIGHT     |



| BARCODE | POWER | BRIGHTNESS | CURRENT | INCANDESCENT<br>LAMP POWER | IP   | MEAS            | CCT   | LIGHT COLOR |
|---------|-------|------------|---------|----------------------------|------|-----------------|-------|-------------|
| 001970  | 36W   | 2900lm     | 180mA   | 290W                       | IP65 | L1200*W53*H28mm | 3000K | WARM WHITE  |
| 001987  | 36W   | 3000lm     | 180mA   | 300W                       | IP65 | L1200*W53*H28mm | 6000K | DAY LIGHT   |